

### PRODUCT DESCRIPTION

STATUS CAR 5W-40 is a high-performance synthetic lubricant designed to ensure maximum protection and durability in high-power engines. Its advanced formulation provides a long service life (Long Life), ensuring excellent performance even under demanding driving conditions.

Thanks to its optimized viscosity grade and the use of state-of-the-art components, this oil minimizes deposit formation and keeps the engine clean, improving its efficiency and extending its service life.

Tests conducted demonstrate high oxidation resistance, as well as minimal sludge and residue formation, contributing to greater internal engine cleanliness and more reliable operation.

It is especially recommended for gasoline and light diesel vehicles without exhaust aftertreatment systems (without DPF), including engines from brands such as Mercedes-Benz, Porsche, VW/Audi, and Renault, especially in high-performance or demanding driving applications.

Its excellent thermal stability and synthetic base allow for extended oil change intervals, reducing maintenance costs without compromising engine protection.

#### Key Benefits

- Synthetic oil 5W-40 Long Life
- Excellent protection in high-power engines
- High oxidation resistance
- Reduces sludge and deposit formation
- Keeps the engine clean and efficient
- High thermal stability under extreme conditions
- Allows extended change intervals
- Compatible with gasoline and light diesel engines without DPF
- Recommended for Mercedes-Benz, Porsche, VW/Audi, and Renault

### PRESENTATION

BULK	109059
1000 LTS.	100212
200 LTS.	100213
50 LTS.	100214
20 LTS.	100215
5 LTS.	100216
4 LTS.	106315
1 LT.	100217





### QUALITY LEVEL

ACEA A3/B4  
API:SN/CF  
GM-LL B-025  
MB 229.5  
VW 502.00/505.00  
BMW LL-01  
Renault RN 0700/0710  
FIAT 9.55535-M2  
Peugeot&Citroën B712296  
Porsche A40



EELQMS  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

### TECHNICAL PROPERTIES

trad_Propiedad	trad_Valor
SAE GRADE	5W-40
VISCOSITY AT 100°C	12,50 - 16,3
VISCOSITY AT -30°C	<6600
HTHS AT -150°C	>3,5
VISCOSITY INDEX	160
FLASH POINT	227
POUR POINT	-39
SULPHATED ASH	<1,6
TBN	>10,0



### SAFETY AND HYGIENE TRANSLATED

Safety Data Sheets are available upon request and should be consulted for detailed information on the correct handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations. — translated





### IMPORTANT NOTE TRANSLATED

The information presented is based on current production data and may vary within specified tolerances. Temperature ranges are provided for guidance only. The information and data contained in this document may be modified without prior notice. This information supersedes and voids all previous editions. — translated



EELQMS  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

