

PRODUCT DESCRIPTION

High-performance mineral diesel engine oil, specially formulated to provide excellent protection and durability across a wide range of heavy-duty applications. Designed for modern and traditional diesel engines, it ensures reliable lubrication even under demanding operating conditions.

This lubricant is compatible with Euro II, Euro III, and some Euro IV low-emission engines, providing an optimal balance between engine cleanliness, deposit control, and oxidation resistance.

Recommended for:

Heavy transport trucks

Public works and construction machinery

Off-road equipment

Mixed fleets (diesel and gasoline)

Thanks to its advanced formulation, it offers:

Excellent wear protection

High thermal stability

Effective soot and deposit control

Extended engine life

PRESENTATION

BULK	109190
1000 LTS.	100400
200 LTS.	100401
50 LTS.	100402
20 LTS.	100403
5 LTS.	100404
4 LTS.	105810
1 LT.	105860



QUALITY LEVEL

API:CI-4/SN

ACEA A3/B4 & E7

MAN M3275

IVECO-PEGASO

DAF XF; Renault RLD-2

MB 229.1/228.3

Scania LDF

Volvo VDS-3

Deutz DQC III-10



**TECHNICAL PROPERTIES**

trad_Propiedad	trad_Valor
SAE GRADE	15W-40
VISCOSITY AT 100°C	12,50 - 16,3
VISCOSITY AT -2°C	<7000
HTHS AT 150°C	>3,5
VISCOSITY INDEX	150
FLASH POINT	205
POUR POINT	-38
SULPHATED ASH	<2,0
TBN	>9,9

SAFETY AND HYGIENE

Safety Data Sheets are available upon request and should be consulted for detailed information on the correct handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations. — translated

IMPORTANT NOTE

The information presented is based on current production data and may vary within specified tolerances. Temperature ranges are provided as guidance only. The information and data contained in this document may be modified without prior notice. This information replaces and voids all previous editions. — translated

