STATUS GLOBAL

10W-40

ENGINE OIL · PASSENGER CAR · SYNTHETIC TECHNOLOGY

DESCRIPTION

STATUS GLOBAL 10W-40 is a high-performance synthetic-technology engine oil developed with Full SAPS technology and latest-generation base oils to deliver maximum protection for modern petrol and diesel engines. It meets the demanding ACEA A3/B4 and APISN/CI-4 specifications and meets the requirements of GM-LL B-025 · Renault RN0700 / RN0710 · VW 502.00/505.00 · MB 229.1 · FIAT 9.55535-G2.

It is recommended for high-performance petrol and diesel engines not fitted with a particulate filter.

Its outstanding thermal stability and high viscosity index maintain a robust lubricating film from cold start-up to high operating temperatures, reducing wear, oxidation and deposit formation. The result is a cleaner engine, lower fuel consumption and extended engine life and oil-change intervals, even under the most demanding driving conditions.



QUALITY LEVEL

- **ACEA A3/B4**
- **APISN/CI-4**
- **GM-LL B-025**
- **Renault RN0700 / RN0710**
- **VW 502.00/505.00**
- **MB 229.1**
- **FIAT 9.55535-G2**

APPLICATIONS

- It is recommended for high-performance petrol and diesel engines not fitted with a particulate filter.
- Vehicles requiring ACEA A3/B4 and APISN/CI-4.
- Standards level: GM-LL B-025 · Renault RN0700 / RN0710 · VW 502.00/505.00 · MB 229.1 · FIAT 9.55535-G2.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

UPDATED: 22/09/2026

Made in Spain

SASH LUBRICANTS®

STATUS GLOBAL

10W-40

ENGINE OIL · PASSENGER CAR · SYNTHETIC TECHNOLOGY

TECHNICAL PROPERTIES

	ASTM METHODS	
SAE Grade		**10W-40**
Viscosity at 100 °C (cSt)	ASTM D-445	**12,50 - 16,3**
CCS viscosity at -25 °C (cP)	ASTM D-5293	**<7000**
HTHS at 150 °C (mPa·s)	ASTM D-5481	**> 3,5**
Viscosity index	ASTM D-2270	**150**
Flash point (°C)	ASTM D-92	**222**
Pour point (°C)	ASTM D-97	**-38**
Sulphated ash (%)	ASTM D-874	**<1,6**
Phosphorus (%)	ASTM D-5185	**0,08 - 0,10**
Sulphur (%)	ASTM D-5185	**< 0,4**
TBN (mg KOH/g)	ASTM D-2896	**>10,0**

PACKAGING

Bulk	IBC 1000 L	Drum 200 L	Drum 50 L	Drum 20 L	Box 4x5 L	Box 4x4 L	Box 12x1 L
Ref. 109181	Ref. 100200	Ref. 100201	Ref. 100202	Ref. 100203	Ref. 100204	Ref. 106233	Ref. 100205

Minimum order (MOQ) · Box 4x4 L: 72 boxes. Other formats: subject to availability. Bulk on request.

NOTES

The information shown is based on current production data and may vary within the given tolerances. The temperature range is given as a general guide. Information and data may be modified without prior notice. This information supersedes previous editions.

SAFETY & HYGIENE

Safety Data Sheets (SDS) are available on request and should be consulted for appropriate information on handling, storage and disposal. The company shall not be liable for damage caused by improper use of the product or by failure to take the specified precautions. Keep out of the reach of children. Avoid prolonged skin contact and use suitable protective equipment. Do not pour into soil, drains or watercourses; used oil must be handed over to an authorised waste manager.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com