ATF DRAIVER DEXRON IIIH

LUBRICANT · AUTOMATIC TRANSMISSION · 100% SYNTHETIC

DESCRIPTION

ATF DRAIVER DEXRON IIIH is a high-performance 100% synthetic automatic transmission fluid developed for automatic transmissions, torque converters, dual-clutch and continuously variable gearboxes. It meets the demanding specifications and holds the Allison C-4 Fluids, Allison TES, 389 · Caterpillar TO-2 Fluids · Chrysler transmissions prior to Chrysler MS-9602 or MS-7176 · Ford MERCON®; Ford M2C138-CJ, M2C 166-H Fluids · GM DEXRON® III-H, III-G, III-F, III-E, III-D · MAN 339 Z1 and V1, Z2 and V2 · MB 236.1, 236.5, 236.6, 236.7, 236.9 · Voith 55,6335 and 55,6336; Volvo 97340, 97341 · ZF TE-ML 02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C approvals.

Its stable friction coefficient ensures smooth, precise shifting throughout the fluid life, preventing clutch slip and converter shudder. Its high thermal and oxidation stability protects gears, bushings and solenoid valves against varnish and deposits, while excellent cold fluidity ensures immediate response from start-up.

APPLICATIONS

- Automatic transmissions, torque converters, DCT and CVT gearboxes.
- Passenger cars, vans and commercial vehicles as approved.
- Meets ; approvals Allison C-4 Fluids, Allison TES, 389 · Caterpillar TO-2 Fluids · Chrysler transmissions prior to Chrysler MS-9602 or MS-7176 · Ford MERCON®; Ford M2C138-CJ, M2C 166-H Fluids · GM DEXRON® III-H, III-G, III-F, III-E, III-D · MAN 339 Z1 and V1, Z2 and V2 · MB 236.1, 236.5, 236.6, 236.7, 236.9 · Voith 55,6335 and 55,6336; Volvo 97340, 97341 · ZF TE-ML 02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C.



QUALITY LEVEL

- **Allison C-4 Fluids, Allison TES, 389**
- **Caterpillar TO-2 Fluids**
- **Chrysler transmissions prior to Chrysler MS-9602 or MS-7176**
- **Ford MERCON®; Ford M2C138-CJ, M2C 166-H Fluids**
- **GM DEXRON® III-H, III-G, III-F, III-E, III-D**
- **MAN 339 Z1 and V1, Z2 and V2**
- **MB 236.1, 236.5, 236.6, 236.7, 236.9**
- **Voith 55,6335 and 55,6336; Volvo 97340, 97341**
- **ZF TE-ML 02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C**

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com

ATF DRAIVER DEXRON IIIH

LUBRICANT · AUTOMATIC TRANSMISSION · 100% SYNTHETIC

TECHNICAL PROPERTIES

		ASTM METHODS
Viscosity at 100 °C (cSt)	ASTM D-445	**6.5 - 7.5**
Viscosity index	ASTM D-2270	**170**
Flash point (°C)	ASTM D-92	**226**
Pour point (°C)	ASTM D-97	**-50**

PACKAGING

Bulk	IBC 1000 L	Drum 200 L	Drum 50 L	Drum 20 L	Box 4x5 L	Box 4x4 L	Box 12x1 L
Ref.	Ref. 100863	Ref. 100864	Ref. 100865	Ref. 100866	Ref. 100867	Ref. 105800	Ref. 100868

Minimum order (MOQ) · Box 4x4 L: 72 boxes. Other formats: subject to availability. Bulk on request.

NOTES

The information shown is based on current production data and may vary within the given tolerances. The temperature range is given as a general guide. Information and data may be modified without prior notice. This information supersedes previous editions.

SAFETY & HYGIENE

Safety Data Sheets (SDS) are available on request and should be consulted for appropriate information on handling, storage and disposal. The company shall not be liable for damage caused by improper use of the product or by failure to take the specified precautions. Keep out of the reach of children. Avoid prolonged skin contact and use suitable protective equipment. Do not pour into soil, drains or watercourses; used oil must be handed over to an authorised waste manager.

sash@lubricantes-sash.com
+34 961 464 843
www.lubricantes-sash.com