

DESCRIPTION

STATUS CAR 5W-30 is a long-life synthetic lubricant oil developed to offer excellent engine protection under all types of usage conditions. Thanks to its carefully studied viscosity, it acts effectively both during cold start and at high operating temperatures, helping to reduce wear on internal engine components.

Its formulation also contributes to reducing fuel consumption and stands out for its low oil consumption over kilometers, making it a reliable option for drivers seeking performance, protection, and durability.

It is especially suitable for gasoline or light diesel engines equipped with modern technologies such as Common Rail injection, variable intake multivalve engines, Valvetronic systems, turbochargers, and other advanced configurations.

Important: this lubricant is not suitable for engines equipped with DPF particle filters.

Key benefits

- Synthetic 5W-30 Long Life oil
- Excellent protection in cold and hot conditions
- Helps reduce engine wear
- Promotes fuel savings
- Low oil consumption
- Suitable for gasoline and light diesel engines
- Recommended for engines with Common Rail, turbo, multivalve, and Valvetronic
- Not compatible with engines with DPF

PRESENTATION

BULK	109182
1000 LTS.	100218
200 LTS.	100219
50 LTS.	100220
20 LTS.	100221
5 LTS.	100222
4 LTS.	105629
1 LT.	100228





QUALITY LEVEL

ACEA A3/B4
API:SN/CF
GM-LL B-025
VW 502.00/505.00
BMW LL-01
Renault RN 0700/0710
MB 229.5
FIAT 9.55535-G1
Peugeot & Citroën B712296

TECHNICAL PROPERTIES

trad_Propiedad	trad_Valor
SAE GRADE	5W-30
VISCOSITY AT 100°C	9,3 - 12,5
VISCOSITY AT -30°C	<6600
HTHS AT-150°C	>3.5
VISCOSITY INDEX	150
FLASH POINT	226
POUR POINT	-39
SULPHATED ASH	<1,6
TBN	>10,0

SAFETY AND HYGIENE

Safety Data Sheets are available upon request and should be consulted for detailed information on the correct handling and use of the product. The company is not responsible for damages resulting from improper use or failure to comply with the indicated precautions and recommendations. — translated





IMPORTANT NOTE

The information presented is based on current production data and may vary within specified tolerances. Temperature ranges are provided as guidance only. The information and data contained in this document may be modified without prior notice. This information replaces and voids all previous editions. — translated



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

