CLASSIC B - ALOFIT - UV OIL
A13864



Dimension board

LENGTH	1900 mm
WIDTH	190 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	Min 7 Pl x 1900 mm

Dimension pack

PACK LENGTH	1910 mm
PACK WIDTH	200 mm
PACK THICKNESS	120 mm
PACK WEIGHT	24 kg
LAYERS/BOX	8
M²/PACK	2.89 m²

Dimension pallet

PALLET LENGTH	1930 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1080 mm
PALLET WEIGHT	960 kg
PACKS/PALLET	40
M²/PALLET	115.60 m²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC B
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	UV Olie
SURFACE STRUCTURE	Antique

Composition of the support

SUPPORT TYPE	Lariks
WOOD SPECIES SUPPORT	Berk
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM

Drop click

APPLICATIONS

Light household use.
Moderate commercial use.
Normal commercial use.
Normal household use.
Intensive commercial use.

UNDERFLOOR HEATING

Yes

RE-SANDABLE

Yes

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

CLASSIC B - ALOFIT - UV OIL
A13864

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION

EN 14342

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.