

WORLDWIDE LIGHTWEIGHT UL RATED TL-30 COMPOSITE HIGH SECURITY SAFES

UL Listed TL-30 Construction

- Fire Resistant
- Weighs 30% less than comparable size safes
- Easily transported in elevators of upper levels with floor load limits
- Auto Bolt Detent
- Glass Plate Relocking System
- Heavy-duty ball bearing self-lubricating hinges
- Round Custom milled handle
- Dark Gray Paint Finish
- Adjustable Shelving

Exceeds all latest UL Testing and design specifications with new state of the art bolt/locking mechanism.

Options

- Electronic Access Control Safe Locks
- Lockable Compartments
- Custom Interiors



WORLDWIDE SAFE: Advanced security built to meet and exceed your requirements while providing you, the valued customer, with ultimate peace of mind.

Worldwide Safe & Vault is one of the largest providers of **UL RATED** (Underwriter Laboratories) Safes and Modular Vaults, across the US, Canada and the Caribbean.

All of our **UL RATED** safes are strenuously tested by Underwriter Laboratories and exceed the most current testing standards.

Our **UL RATED** Safes and Modular Vaults **GUARANTEE** insurability with US and overseas insurance companies and underwriters. Safes without UL Ratings DO NOT guarantee insurability.

Worldwide Safe is a turnkey provider, **shipping, delivering, and installing globally**. We also provide **24/7 service**, including after hours and emergency service.

WORLDWIDE LIGHTWEIGHT UL RATED TL-30 COMPOSITE HIGH SECURITY SAFES



FIRE RESISTANT SAFE RATED 350° - 1.5 HOURS

This safe was tested by the manufacturer at an independent laboratory in a furnace at temperatures up to 1850° F, Interior Temperature did not exceed 350.

MODEL	INSIDE DIMENSIONS			OUTSIDE DIMENSIONS			WEIGHT	SHELF	CUBIC CAP.
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH			
WWS-1814	18"	14"	12"	22"	18"	24"	470 LBS.	1	1.8
WWS-2518	25"	18"	14"	29"	18"	26"	670 LBS	1	4.20
WWS-3518	35"	18"	21"	39"	22"	33"	1180 LBS	2	7.70
WWS-3524	35"	24"	20"	39"	28"	32"	1350 LBS	3	9.70
WWS-4524	45"	24"	20"	49"	28"	32"	1500 LBS	3	12.9
WWS-5524	55"	24"	20"	59"	28"	32"	1650 LBS	4	15.3
WWS-6020	60"	20"	21"	64"	24"	33"	1810 LBS	4	14.6
WWS-6032	60"	32"	21"	64"	36"	33"	2120 LBS	5	23.3
WWS-6528	65"	28"	20"	69"	32"	32"	2020 LBS	4	21.1
WWS-6536	65"	36"	26"	69"	40"	38"	2680 LBS	5	35.2

ADD 2 1/2" FOR HANDLE AND LOCK PROTRUSION. OUR POLICY IS ONE OF CONSTANT IMPROVEMENT. WE THEREFORE RESERVE THE RIGHT TO INCORPORATE ANY CHANGES WITHOUT PRIOR NOTICE.

DOOR SWING PROJECTIONS

MODEL	A	B	C
WWS-1814	6.5"	41.5"	33.5"
WWS-2518	10.5"	47.5"	41.5"
WWS-3518	10.5"	54.5"	41.5"
WWS-3524	16.5"	59.5"	53.5"
WWS-4524	16.5"	59.5"	53.5"
WWS-5524	16.5"	59.5"	53.5"
WWS-6020	12.5"	56.5"	45.5"
WWS-6032	24.5"	68.5"	69.5"
WWS-6528	20.5"	63.5"	61.5"
WWS-6536	28.5"	77.5"	77.5"

