PRODUCT DATA SHEET

# Q8 Chain Oil 150

*Advanced chain and chainsaw oil*

## Description

*Q8 Chain oil 150 is an advanced chain and chainsaw oil with low oil cosumption and high wear protection through the adhesive oil film. Its excellent components are carefully selected to prevent harmful or unpleasant odours. Q8 Chain oil 150 has optimum wear-, corrosion- and rust protection.*

## Applications

*Q8 Chain Oil 150 is used in chains and slides of chainsaws. It is perfect for chains, slideways and guides in industrial applications.*

## Benefits

- *Improves the durability of the equipment thanks to its characteristics*
- *Advanced adhesive characteristics*
- *Excellent spreadability*
- *Advanced performance against wear*

## Specifications & Approvals

| | |
|---|---|
| **ISO** | 6743-1 L-AC |

## Properties

| | Method | Unit | Typical |
|---|---|---|---|
| *ISO Viscosity Grade* | *-* | *-* | *150* |
| *Density, 15 °C* | *D 4052* | *g/ml* | *0,887* |
| *Colour* | *D 1500* | *-* | *L 2.0* |
| *Kinematic Viscosity, 40 °C* | *D 445* | *mm²/s* | *150.0* |
| *Kinematic Viscosity, 100 °C* | *D 445* | *mm²/s* | *14.60* |
| *Viscosity Index* | *D 2270* | *-* | *96* |
| *Pour Point* | *D 97* | *°C* | *-12* |
| *Flash Point, COC* | *D 92* | *°C* | *262* |
| *Copper Strip, 3 h, 100 °C* | *D 130* | *-* | *1* |

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

## Remarks

*Q8 Chain Oil 150 should not be used for lubricating the engine of the chain saw.*